

# 4820i

## Industrial Cordless 2D Imager



powered by  
**Adaptus**<sup>®</sup>  
imaging technology 5.0

### Overview

From the global leader in handheld imaging solutions, the 4820i Industrial Cordless 2D Imager is designed to provide unmatched data collection performance and versatility for applications that demand maximum reliability in the harshest working environments.

Powered by Adaptus™ Imaging Technology 5.0, the 4820i delivers high-performance, omni-directional linear and 2D bar code reading plus the versatility of digital image capture. With Adaptus 5.0, enterprises have the ability to capture and process more data than ever before with a single device.

Built for scan-intensive applications requiring a ruggedized solution, the 4820i features our highest drop specification and an IP54 rating to guarantee protection against the penetration of dust and liquid. However, unlike other industrial grade solutions, the 4820i features best-in-class ergonomics – ensuring maximum user comfort and productivity.

The 4820i features a unique design that not only allows tool-free access to the battery, but also eliminates the need to dock the scanner for charging – a true advantage for operations where downtime is not an option.

Bluetooth® cordless connectivity allows users to move freely and eliminates the hazard of cables in fast-paced environments – all the while ensuring fast, accurate data communication.

### Premium Features

- **High Performance and Versatile Data Collection:** Adaptus Imaging Technology 5.0 provides aggressive, omni-directional reading of all linear and 2D bar codes, plus enables digital image capture.
- **Tool-Free Battery Access:** Thumbwheel end-cap allows easy access to the battery, permitting employees to quickly swap batteries and keep working instead of docking the scanner for charging – a key feature for operations running multiple shifts.
- **Simplified Device Configuration Through Advanced Software Assets:** Visual Xpress™ software enables device programming and configuration on a host system through an easy-to-use Windows®-based graphical user interface.
- **Leading Combination of Ergonomics and Durability:** Rugged housing is specified to withstand 50 drops from 6.5 feet (2m) and certified to IP54 standards, while still being ergonomic and easy-to-use.
- **Presentation Scanning Capability:** Can be programmed to scan in presentation mode while docked in the base, enabling hands-free scanning.
- **FIPS 140-2 Certification Pending:** In-process for Federal Information Processing Standards (FIPS) certification for wireless data transmission, required by US Government Departments and recommended in private sector and non-US Government applications for sensitive data security.

### Industry Standard Features

- **Wireless Connectivity:** Bluetooth v1.2 radio enables movement up to 33 feet (10m) from the base, and reduces interference with other wireless systems. Up to 7 imagers can communicate to 1 base, reducing the total cost of ownership.
- **User Feedback Designed for Extreme Environments:** Adjustable, extra loud “good read” beeper and dual LED indicators ensure reliable & intuitive feedback even in noisy environments.
- **Long-Lasting Lithium-Ion Battery:** Powers up to 50,000 scans per full charge ensuring maximum uptime.

# 4820i Specifications

## Performance

<b>Illumination LEDs:</b>	626nm +30nm
<b>Green LED Aimer:</b>	526nm +30nm
<b>Image:</b>	VGA, 752x480. Binary, TIFF, or JPEG output.

## Working Range:

	<b>SR</b>	<b>8.3 mil Linear (.021cm)</b>	<b>13 mil UPC (.033cm)</b>	<b>6.6 mil PDF417 (.017cm)</b>	<b>10 mil PDF417 (.025cm)</b>	<b>15 mil Data Matrix (.038cm)</b>	<b>35 mil MaxiCode (.089cm)</b>
<b>Near</b>		3.0 in. (7.6cm)	1.6 in. (4.1cm)	4.0 in. (10.2cm)	2.6 in. (6.6cm)	1.8 in. (4.6cm)	1.5 in. (3.8cm)
<b>Far</b>		7.1 in. (18.0cm)	12.7 in. (32.3cm)	5.7 in. (14.5cm)	8.5 in. (21.6cm)	9.7 in. (24.6cm)	12.5 in. (31.8cm)
	<b>SF</b>	<b>7.5 mil Linear (.019cm)</b>	<b>13 mil UPC (.033cm)</b>	<b>6.6 mil PDF417 (.017cm)</b>	<b>10 mil PDF417 (.025cm)</b>	<b>15 mil Data Matrix (.038cm)</b>	<b>15 mil QR Code (.038cm)</b>
<b>Near</b>		2.0 in. (5.1cm)	1.5 in. (3.8cm)	2.3 in. (5.8cm)	2.2 in. (5.6cm)	1.8 in. (4.6cm)	2.2 in. (5.6cm)
<b>Far</b>		6.0 in. (15.2cm)	8.4 in. (21.3cm)	5.5 in. (14.0cm)	7.1 in. (18.0cm)	7.0 in. (17.8cm)	6.7 in. (17.0cm)

<b>Pitch/Skew Angle:</b>	±40°
<b>Motion Tolerance:</b>	4 in. (10 cm) per second

## Wireless Technology

<b>Frequency:</b>	2.4 to 2.4835 GHz (ISM Band) Frequency-Hopping Bluetooth v. 1.2
<b>Range:</b>	33 ft. (10 m) typical
<b>Data Rates:</b>	720 KBps
<b>Security:</b>	FIPS 140-2 (Certification Pending)

## Battery (Lithium Ion)

<b>Capacity:</b>	1,800 mAh (minimum)
<b>Number of Scans:</b>	50,000
<b>Expected Hours of Operation:</b>	16 hours
<b>Charge Time with 9 VDC External Power Supply:</b>	4 hours for full charge from full discharge

## Symbologies

<b>2 Dimensional:</b>	PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Aztec Mesas, Code 49, and EAN•UCC Composite
<b>Linear:</b>	Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128, UPC, EAN, GS1 DataBar, Codablock and ISBT 128 Concatenation* *requires a paid license
<b>Postal:</b>	Postnet, Planet Code, British Post, Canadian Post, Japanese Post, KIX (Netherlands Post)
<b>OCR Fonts:</b>	OCR-A, OCR-B
<b>Interfaces:</b>	Keyboard wedge, USB, TTL level RS-232, wand emulation, TTL level Serial Wedge, and IBM 46XX retail terminals

## Mechanical/Electrical

	<b>4820i Scanner</b>	<b>2020 Base</b>
<b>Dimensions</b>		
<b>Weight:</b>	9.6 oz. (272 g)	8.8 oz. (250 g) w/o cable
<b>Height:</b>	6.2 in. (15.7cm)	3.1 in. (7.9cm)
<b>Power Requirements</b>		
<b>Input Voltage:</b>	3.7 V internal battery	4.7 to 14 VDC (host) 8.5 to 9.5 VDC external power supply
<b>Current Draw:</b>	-----	125mA max @ 5 V (no charging) 100 mA max @ 12 V (no charging) 825mA max @ 12 V (charging)

## Environmental

	<b>4820i Scanner</b>	<b>2020 Base</b>
<b>Sealing:</b>	IP54	
<b>Operating Temperature:</b>	14° to 122°F (-10° to 50°C)	32° to 122°F (0° to 50°C)
<b>Storage Temperature:</b>	-40° to 158°F (-40° to 70°C)	-40° to 140°F (-40° to 60°C)
<b>Humidity:</b>	0 to 95%, non condensing	up to 95%, non condensing
<b>Mechanical Shock:</b>	Functional after 50 drops from 6.5 ft. (2.0m)	Functional after 50 drops from 3.3 ft. (1m)
<b>Agency:</b>	FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV, 2005 Sunrise Compliant	
<b>Warranty:</b>	3 years (Note: battery warranty is 1 year)	

BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed to Hand Held Products.



### Worldwide Offices

#### NORTH AMERICA

Skaneateles Falls, NY  
Tel: +1 315 685 8945  
or, in North America:  
+1 800 582 4263  
napresales@handheld.com

Carolinas  
Tel: +1 803 835 8000  
or, in North America:  
+1 800 582 4263  
napresales@handheld.com

#### ASIA AND THE PACIFIC RIM

Hong Kong  
Tel: +852 2511 3050  
appresales@handheld.com

Japan  
Tel: +813 5770 6312  
appresales@handheld.com

Shanghai  
Tel: +86 21 6361 3818  
appresales@handheld.com

Malaysia  
Tel: +603-6201 9020  
appresales@handheld.com

#### LATIN AMERICA

Naples, Florida  
Tel: +1 239 263 7600  
lapresales@handheld.com

Rio De Janeiro  
Tel: +55 21 2178 0500  
lapresales@handheld.com

Mexico  
Tel: +52 55 5203 2100  
lapresales@handheld.com

#### EUROPE, MIDDLE EAST, AND AFRICA

Europe  
Tel: +31 (0) 40 29 01 600  
eusales@handheld.com

United Kingdom  
Tel: +44 (0) 1 925 240055  
eusales@handheld.com

Italy  
Tel: +39 02 7254 6754  
Info.italy@handheld.com

France  
Tel: +33 (0) 1 41 158220  
Info.france@handheld.com

Germany  
Tel: +49 (0) 7 477 151377  
Info.germany@handheld.com

Spain  
Tel: +34 93 228 78 68  
Info.spain@handheld.com



Hand Held Products, Inc., ("Hand Held Products")®1999-2007. All rights reserved. Printed in the U.S.A. Web Site Address: www.handheld.com  
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.