

DECLARATION OF CONFORMITY

Manufacturers' Name: Honeywell International Inc Honeywell Scanning and Mobility Fort Mill, SC 29707 USA	European Representative: Honeywell International Inc Honeywell Scanning and Mobility Nijverheidsweg 9-13 Eindhoven, 5627 BT The Netherlands Phone: +31 40 290 16 00
---	---

Honeywell declares under its sole responsibility that the Honeywell products described below conform to Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment, as amended.

Referenced harmonized standards and/or technical specifications:

EN 50581:2012 "Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances"

Additional information:

None

Honeywell Products:

162829-0001	CBL, MPP USB ADPTR
162830-0001	CBL, MPP RS232 ADPTR
162831-0001	CBL, MPP RS232+USB
19-00121	Cable, Straight, Black
19-00122B-3	Cable, Black, Coio 9'
19-00123	Cable, black, USB type A
19-00142C-3	CBL Black 10 Cond Shield
19-00239A-3-10	RS232 cable PWR
19-00264C	Cable, 4225, Shielded Head
19-00277B	Cable, 4225, Head, Dual 8
19-00307-3	Cable MVC Dual Ended 10
19-00314B-3	Cable, Dual Ended USB
19-00335A-3	Cable, Dual Ended Male
19-00336A-3	Cable, Dual Ended RJ
19-00339A-3	Cable, Dual End, DB9
19-00341A-3	Cable, Dual End, USB, Black
19-00362A-3	USB Multi Checkpoint
19-19273	Cable, w/Strain Relief

DECLARATION OF CONFORMITY

19-19670	Cable 14 COND SHLD W/DRA
19-19671	Cable, 8 COND, Shield
19-19753B	CBL KEYWEDGE HEAD W/GRD
19-19805B	Cable, Black, Wdge Adaptor
19-19805B-3	Cable, Black, Wdge Adaptor
19-19825B	Cable, Pwrlnk, Straight
19-19825B-3	Cable, pwrlnk, straight
19-19826	Cable, USB Type A
19-19827A	Cable, Pwrlnk, coiled
41203757-05	CBL, MOD DEC W/NO CONN
41203757-06	CBL, MOD W/O CONN.
41203757-07	CBL, MOD BI W/NO CONN
41205223-05	CBL, 3400+12V CORE ENG
41205571-03	CBL, 10 COND CORE ENGINE
42203758-01E	Cable: RS232 TTL, Power on Pin 9, TX Data on Pin 2 Connector: D 9 PIN M Length: 7.7 ft. (2.4m), coiled
42203758-02E	Cable: RS232 TTL 'EP' Connector: 9 Pin D 9 PIN F, 4 Pin Mini Din Length: 7.7 ft. (2.4m), coiled
42203758-03E	Cable: RS232 TTL, Connector: D 9 Pin F, power on pin 9, TX data on pin 2, coiled Length: 7.7ft. (2.3m)
42203758-03SE	Cable: RS232 TTL, Connector: D 9 Pin F, power on pin 9, TX data on pin 2, straight Length: 7.7ft. (2.3m)
42203758-04E	Cable: RS232 TTL, Connector: D 9 Pin F connector, TX data on pin 2, external power, coiled Length: 7.7ft. (2.3m)
42203758-06E	Cable: RS232 TTL, 9 F 'EP' 15', D 9 PIN F, Mini Din 4 PIN Length: 7.7 ft. (2.3m), coiled
42203764-03E	Cable: Wand Emulation, Power on Pin 9 Connector: D 9 PIN Squeeze Length: 7.7 ft. (2.3m), coiled
42203764-04E	Cable: Wand Emulation, power on Pin 4 Connector: D 9 PIN Squeeze Length: 6.8 ft. (2.0m), coiled
42204064-01E	Cable: IBM 3151.3471.3472, Connector: Modular 8 PIN M/F Length: 8.5 ft. (2.6m), coiled
42204253-01E	Cable: RS232, Power on Pin 9, TX Data on Pin 2 Length: 7.7 ft. (2.4m), coiled
42204253-03E	Cable: RS232, power on Pin 9, TX Data on Pin 2 Connector: D 9 PIN F Length: 7.7 ft. (2.4m), coiled
42204253-04E	Cable: RS232, black, TX Data on Pin 2 Connector: D 9 PIN F and Mini Din 4 PIN F, 2.3m (7.7'), coiled, external power
42204253-05E	Cable: RS232, black, TX Data on Pin 2 Connector: D 9 PIN F and Mini Din 4 PIN F, 5.0m (16.3'), coiled, external power
42204253-22E	Cable: RS232, black, TX Data on Pin 2 Connector: D 9 PIN M/F and Mini Din 4 PIN F, 6.8m (22.3'), coiled, external power
42204841-01E	Cable: direct connect, Connector: Mini Din 6 PIN M Length: 7.7 ft. (2.3m), coiled
42204254-01E	CBL, 55/30.RS232, 25PIN MALE
42204906-01E	Cable: 55/30 extender Cable: Connector: Modular 8 PIN M/F, coiled
42204933-01E	Cable: Wand Emulation, Connector: Din 5 PIN M (w/ lock) Length: 6.8 ft. (2.1m), coiled
42205021-01E	Cable: AT - PS/2 & Compatibles, EP, wedge (3.0ft. .91m), straight
42205155-02E	Cable: IBM 46xx, black, RS485 Port 9A/B, 3.7m (12.2'), coiled, Connector: SDL 4 PIN A Key
42205155-04E	Cable: IBM 46xx, black, RS485 Port 9A/B, 7.0m (23.0'), coiled
42205155-05E	Cable: IBM 46xx, black, RS485 Port 9A/B, 3.1m (10.2'), coiled

DECLARATION OF CONFORMITY

42205626-03E	Cable: RS232, black, DB9, 2.3m (7.7'), external power, coiled
42205895-01E	Cable: RS232 TTL, black, coiled, 2.3m (7.7'), power from PS-2 keyboard/mouse port
42205910-04E	Cable, RS-232, EP Connector: 9 PIN D F Length: 4.2 ft. (1.3m), straight
42205978-01E	Cable: HHLC/laser emulation Connector: D 9 PIN Squeeze Length: 6.8 ft. (2.0m), coiled
42206090-01E	Cable: RS232 TTL out Mod 8 Pin M Length: 7.7 ft. (2.4m), straight
42206092-01CE	Cable: AT - PS/2 & compatibles ESD/cleaned, wedge Connector: Mini Din 6 PIN M/F Length: 7.0 ft. (2.1m)
42206132-01E	Cable: AT - PS/2 & compatibles wedge, EP, Connector: Mini Din 6 PIN F Length: 15.5 ft. (4.7m), straight
42206132-02E	Cable: AT - PS/2 & compatibles, wedge Connector: Mini Din 6 PIN M/F Length: 9.2 ft. (2.8m), coiled
42206132-02SE	Cable: AT - PS/2 & compatibles, wedge Connector: Mini Din 6 PIN M/F Length: 9.2 ft. (2.8m), straight
42206132-03E	Cable: AT - PS/2 & compatibles wedge, EP Connector: Mini Din 4 PIN F Length: 9.2 ft. (2.8m), straight
42206139-04E	100, 3900 RS232 TTL
42206161-01E	Cable: USB, black, Type A, 2.6m (8.5'), straight, host power
42206162-01E	Cable: USB, black, 12V locking, 2.6m (8.5'), straight, host power
42206200-01E	Cable: coiled direct connect 3800-II connector Connector: Din 7 PIN M (with lock) Length: 15.7 ft. (4.8m)
42206202-01E	Cable: USB, black, secondary interface Length: 9.2 ft. (2.8m), coiled
42206202-02E	Cable: USB, black, Type A, 2.8m (9.2'), coiled, host powered
42206202-03E	Cable, USB 12 Ft
42206203-04E	CBL, 5600 RETAIL USB
42206212-02E	Cable: Combo kit with resistor Connector: Mini Din or Din PCs and PS/2 Length: 9.2 ft. (2.8m)
42206236-01E	Cable: 3800 Direct Connect Length: 7.7 ft. (2.4m), coiled
42206287-01E	Cable: RS232 TTL, power on Pin 9 + 12 VDC Connector: D 9 PIN F Length: 7.7 ft. (2.3m), coiled
42206300-01E	Cable, RS-232 TTL output, Connector: D 9 PIN M Length: 7.7 ft. (2.4m), coiled
42206301-01E	Cable: RS232 serial out, coiled
42206338-01E	Dolphin Series straight USB charging and communications cable (not compatible with 3800g)
42206339-01E	Dolphin Series RS-232 charging and communications cable
42206383-01E	NCR 7875, 3800
42206415-01E	CABLE, KEYBOARD EMULATION CUSTOM
42206416-01E	Cable: USB, black, Type A, coiled, 2.6m (8.5'), external power
42206422-01E	Cable: RS232 TTL, black, DB9, 2.3m (7.7'), straight, 5v external power
42206429-01E	Cable, RS232 TTL, 9 PIN
42206430-01E	Cable, Commercial USB
42206431-01E	Cable: USB, black, Type A, 3.4m (11.1') coiled, host power (Use w/3800VHD-ESD-12E. Not compatible with 3800g)
42206433-01E	Cable: USB, +5V, 8.5FT, straight cable ending in right angle (8.5ft, 3.7m)
42206437-01E	Cable, Retail USB
42206457-01E	Cable, USB, 15' Coiled
42206460-01E	Cable RS232 W/EP, 4600G
425388-0406	CABLE, USB A MALE TO USB

DECLARATION OF CONFORMITY

427508-0630	CBL ASSY, MINI DNG M/F
427518-0913	CBL ASSY, D9 M/F 1:1 ST
50101274-001	Cable Black Coiled
50101275-001	Cable DUAL Ended Male
50101284-001	Cable,VSD,3310G
50109842-001	Cable, MB TO HUB 40pin
50111776-001	NGB CBL MB TO VHUB WITH
50111778-001	NGB CBL WIRE HARNESS SA
50113738-001	NGB MB TO IMAGER CBL
50118069-001	USB Multi Checkpoint
50118071-001	RS232 Multi Checkpoint
50126968-001	USB cable, 2.4m
50126968-004	USB Cable, 3M
50130643-001	AUTCUBE MAIN TO VLD PCBA CBL ASSY
50133276-002	AutoCube Cable, Display, USB, 3m
50133835-001	Wire Harness, twisted, 10pin, ECAP, 1920i
50134004-001	Cable, Grounding, TPH
50135246-001	Cable with Bracket Assy HP
50136415-001	Cable, TPH and Ground Length=60cm
52-52511	Cable: Checkpoint EAS, 0.6m (2.0'), straight
52-52556	Cable: Checkpoint EAS, 1.8m (6.0'), straight
52-52557-3-FR	Cable: RS232, black, DB9, 5V, 2.9m (9.5') straight
52-52557A-3-FR	MS4980 RS232 Straight
52-52558-3-FR	Cable: KBW, black, 3.0m (9.8'), coiled, 5V external power with ferrite
52-52558A-3-FR	MS4980 Keyboard Wedge
52-52559-3-FR	Cable: USB, black, Type A, straight, 5V external power with ferrite
52-52559-N-3-FR	Cable: USB, black, Type A, 5V, 2.9m (9.5') straight
52-52559A-3-FR	MS4980 USB Type A
52-52559A-N-3-FR	MS4980 USB Type A
52-52561-3-FR	Cable: USB, black, Type A, 5V, 2.9m (9.5') straight, External IO
52-52561A-3-FR	Cable, Vuquest 33xx USB
52-52562-3-FR	Cable: RS232, black, DB9, 5V, 2.9m (9.5') straight, External IO
52-52562A-3-FR	Cable, Vuquest 33xx RS232
52-52861A	CABLE: USB OPTIMUS CRADLE
52-52828-3	Cable: USB, black, Type A to Type B
52-52828C-3	Cable, USB, Navigator, BT
53-53000-3	Cable: RS232, black, DB9 female, 2.9m (9.5'), coiled, 5V external power
53-53000-N-3	Cable: RS232, black, DB9 female, 2.9m (9.5'), coiled, host power
53-53000H-3	Cable, 9500, RS232, Coil

DECLARATION OF CONFORMITY

53-53002-3	Cable: KBW, black, 2.9m (9.5'), coiled, 5V external power
53-53002-N-3	Cable: KBW, black, 2.9m (9.5'), coiled, host power
53-53002G-3	Cable, Black, Wedge, Coil
53-53002G-N-3	Cable, Black, Wedge, Coil
53-53004-I2	Cable: RS232 Aux, gray, RJ45, 3.8m (12.5'), coiled, 5V external power
53-53004-N-3	Cable: RS232 Aux, black, RJ45, 2.9m (9.5'), coiled, host power
53-53004B-N-3-I2	Cable, RS232, Coil, NO
53-53004C-I2	Cable, 3.5 meter RS232
53-53014-3	Cable: RS232, black, 2.9m (9.5'), coiled, 5V external power
53-53020-3	Cable: Single keyboard cable, black, 2.9m (9.5'), coiled, 5V external power
53-53020-N	Cable: Single keyboard cable, black, 2.9m (9.5'), coiled, host power
53-53020C-3	Cable, Stand Alone KB
53-53068-N-3	Cable: USB, black, 5V Locking, 3.9m (12.8'), coiled, host power
53-53089-3	Cable: RS232, black, 2.9m (9.5'), coiled, 5V external power
53-53089F-3	Cable, Powerlink, RS232
53-53124-3	Cable: RS232, black, DB9 female, 3.7m (12.1'), coiled, 5V external power
53-53101B-3	Cable, RS232, Coil
53-53109D-3	Cable, Powerlink, LSO, coil
53-53125-3	Cable: RS232, black, DB9 female, 6.1m (20.0'), coiled, 5V external power
53-53125C-3	Cable, RS232 Coil, Powerlnk
53-53153-N-3	Cable: RS232 Wincor, black, DB9 male, 2.9m (9.5'), coiled, host power
53-53153C-3	Cable, POWERLINK, RS232
53-53153C-N-3	Cable, RS232 Coiled
53-53213-N-3	Cable: USB, black, 12V locking, 2.9m (9.5'), coiled, host power
53-53213-N-3-FR	Cable: USB, black, 12V locking, 2.9m (9.5'), coiled, host power with ferrite
53-53213D-N	Cable, USB Plus Pwr
53-53213D-N-3-FR	USB A plus power coil
53-53214C-N-3-FR	USB plus power FS only
53-53235-3	Cable: USB, black, Type A, 2.9m (9.5'), coiled, 5V external power
53-53235-N-3	Cable: USB, black, Type A, 2.9m (9.5'), coiled, host power
53-53235-N-3-FR	Cable: USB, black, Type A, 2.9m (9.5'), coiled, host power with ferrite
53-53235G-3	Cable, USB Type A
53-53235G-N-3	CABLE,USB LS,COIL,DIRECT Ruby Grey
53-53235G-N-3-FR	Cable USB A type- Black
53-53283-N-3	Cable: USB, black, Type A, 3.8m (12.5'), coiled, host power
53-53283-N-3-I5	Cable: USB, black, Type A, 4.6m (15.1'), coiled, host power
53-53283C-N-3	Cable, USB A, FS,Coil
53-53290-N-3	Cable: RS232, black, DB9 male, 3.9m (12.8'), coiled, host power
53-53290C-N-3	Cable, RS232, COIL, DB Male

DECLARATION OF CONFORMITY

53-53317A-3	Cable, 8 Pos AUX Cable
53-53802-N-3	Cable: KBW, black, 2.9m (9.5'), coiled, host power
53-53802C-N-3	Cable, GSL KBW Coiled No
53-53809-N-3	Cable: USB, black, Type A, 2.9m (9.5'), coiled, host power
53-53809-N-3-16	Cable: USB, black, Type A, 4.9m (16.0'), coiled, host power
53-53809C-N-3	Cable, USB Type A No
53-53813D-N-3-11.5	USB coil, no powerlink
54-54073-3	Cable: Y type BT FS USB plug connector, straight
54-54088A-3	Cable, strt, RS232, pwrlnk
54-54165-3	Cable: USB, black, Type A, straight, 5V external power
54-54165A-3	Cable Powerlink shielded
54-54235B-3	Cable, SHLD USB A
54-54235B-N-3/9.5	Cable USB Type A black
54-54298B	RS232/LP COMM Cable
54-54667-14	Cable: RS232 LSD, gray, 4.3m (14'), straight, 5V external power
54-54667A-14	LSD RS232 PWRLNK cable
55-55000-3	Cable: RS232, black, DB9 female, 2.9m (9.5'), coiled, 5V external power
55-55000C-3	Cable RS232, 9-PIN
55-55002-3	Cable: KBW, black, 2.4m (7.9'), straight, 5V external power
55-55002C-3	Cable, KBW w/PWR AT
55-55004A-N-3	Cable Black, no powerlink
55-5103A-N-3-KY	5145, RS232 CONN Cable
55-55146-3	CABLE,RS232SRT, LONGSRSPEC DB9
55-55165-3	Cable: USB, black, Type A, 1.5m (4.9'), straight, 5V external power
55-55235-N-3	Cable: USB, black, Type A, 2.9m (9.5'), straight, host power
55-55235C-N-3	CABLE,5145 USB Straight, Type A 2.9M black
55-55284A-N-3-KY	5145, USB, TYPE A Cable
55-55285A	Cable, 5145 RS232
55-55285A-3-KY	5145, RS232, PWRLNK Cable
55-55286A-N-3-KY	5145, KBW Cable
55-55288A-3	Straight .8 pos mod
55-53213D-N-3	Cable, 9500, USB+A 3M
55-55535-N-3	Cable: KBW, black, Type A, 1.9m (5.7'), straight, host power
55-55535C-N-3	USB Type A 1.9m cable
55-55809-N-E-3	Cable: USB, black, Type A and 2 wire pigtail, straight, host power with EAS
55-55809B-N-E-3	Cable, GSL USB EAS NO
57-57000-N-3	Cable: RS232, black, DB9 female, 3.6m (11.8'), straight, no power
57-57004-N-3	Cable: IBM 46xx, black, 4-pin SDL, straight, no power

DECLARATION OF CONFORMITY

57-57006-N-3	Cable: USB, black, Type A, 3.6m (11.8'), straight, no power
57-57006B-N-3	Cable, USB Type A, Black
57-57008-N-3	Cable: StratosSchool, RS232 Aux, black, straight, host power
57-57000F-N-3	Cable, RS232 No Pwrlink
57-57089D-N-3	Cable,RS232 No Pwrlink
57-57099-3	Cable: RS232 Aux, black, 10-pin RJ45, 2.9m (9.5'), straight, host power (voyager/eclipse)
57-57099-3-I2	Cable: RS232 Aux, black, 10-pin RJ45, 3.7m (12'), straight, host power (voyager/eclipse)
57-57099B-3	Cable AUX Port Black
57-57099B-3-I2	12 Feet Stratos AUX
57-57153B-N-3	Cable, RS232 5 Meter No
57-57170-3-5.5C	Scanner AUX cable RS232
57-57200-N-3	Cable: USB, black, 12V locking, 2.7m (8.9'), straight, no power with ferrite
57-57201-N-3	Cable: USB, black, Type A, 4.0m (13.1'), straight, no power with ferrite
57-57201A-N-3	Cable,StratosS,USB,Type
57-57210-N-3	Cable: RS232, black, DB9 female, 3.6m (11.8'), straight, no power
57-57210B-N-3	Cable, RS232 12' No
57-57212B-N-3	Cable, StratosS,IBM, Black
57-57227-N-3	Cable: USB, black, 12V locking, 4.0m (13.1'), straight, no power
57-57227B-N-3	Cable, StratosS, USB A+
57-57312B-3	Cable,EAS-Checkpoint
57-57499A-3	Cable 7800 RS232 Aux
58-58056-N-3	Cable: SING END,2 FT,KB
59-59000-3	Cable: RS232, black, DB9, 2.9m (9.5'), straight, 5V external power
59-59000-3-YJ	Straight, Cord W/PWR
59-59000C-E-3	Cable, RS232EAS STRAIGHT
59-59000G	Cable, RS232 Straight Pwr
59-59000G-3	Cable RS232 Straight pwr
59-59000G-N-3	Cable RS232 Straight No
59-59002-3	Cable: KBW, black, 2.4m (7.9'), straight, 5V external power
59-59002-N-3	Cable: KBW, black, 2.4m (7.9'), straight, host power
59-59002F-3	Cable, KBW, Powerlink
59-59002F-N-3	Cable, KBW, No Powerlink
59-59014-FR	Cable: RS232 MetroSet cable, gray, straight, 5V external power with ferrite
59-59068D-N-3	Cable, STRT,USB 5V, No
59-59084-N-3	Cable: USB, black, Type A, 2.9m (9.5'), straight, host power
59-59084B-N-3	Cable, USB, 3 meter, Type A
59-59095A-N-3	USB Type A straight
59-59153A-N-3-I2WN	Cable, RS232, STRT, SBR
59-59153B-N-3-I2	Cable, RS232, STRT, SBR

DECLARATION OF CONFORMITY

59-59194-N-3-14	Cable: RS232, black, 4.3m (14.1'), straight, host power
59-59194C-N-3-14	Cable RS232 14FT STRT NO
59-592000-N-3	Cable, USB 5V Plus
59-59213A-N-3-FR	Cable, USB A+PWR, 3 meter
59-592350-N	Cable, USB Type A, gray
5S-5S0000-3	Cable, RS232 12V Link
5S-5S002C-3	Cable, KBW 12V LINK
5S-5S0060-N-3	Cable, 46xx 12V direct
5S-5S088A-3	7580 6 pos RS232
5S-5S153B-N-3-10	7800 RS232 Straight No
5S-5S213-N-3	Cable: USB, black, 12V locking, 2.9m (9.5'), straight, host power
5S-5S213D-N-3	Cable, USB Plus Power No
5S-5S253A-3	7820 RS232 straight 12v
5S-5S2350-3	Cable, USB 12V Powerlink
60S-DB9CABLE	D60S DB9 cable
60S-DEXCABLE	D60S DEX cable
7600-RS232 E	Dolphin 7600 RS-232 charging and communications cable
7600-USB E	Dolphin 7600 USB charging and communications cable
80000355E	6 ft. (1.8m) USB Cable
8300051CABLE	8FT POWERSCAN CABLE, D9F
9000052CABLE	CABLE, COMBO, 1FT, USB MASTER, ETHRNT, D15 TO RJ45 AND USB-A
9000054CABLE	CABLE, 12 FT, INPUT POWER
9000063CABLE	CABLE, 6 FT, UPS BATTERY, REMOTE
9000072CABLE	CABLE, COMBO, 1FT, DUAL PS2 ADAPTR, D9 TO DUAL MIN-DIN
9000075CABLE	CABLE, COMBO, 1FT, VX6-VX7 D15 TO RJ45, USB-A, USB-A PLUG
9000076CABLE	MX3Plus Headset coiled adapter cable, includes quick disconnect headset connector to a 2.5 mm audio jack. A headset is still required.
9000077CABLE	CABLE, 1 FT, ADAPTR, POWER, VX1, VX2, VX4, VX6, VX7
9000A054CBL609D9	Cable, Serial Null Modem, PC, D9F to D9F, 6ft, ActiveSync
9500-RS232-1E	Dolphin Series RS-232 charging and communications cable, power supply, and cord (U.S. kit)
9500-USB-1E	Dolphin Series USB charging and communications cable, power supply, and cord (U.S. kit)
A023801	SAT401 EXTENSION CABLE - 5M
A023802	SAT401 EXTENSION CABLE - 10M
A023803	SAT401 EXTENSION CABLE - 15M
A023804	SAT401 EXTENSION CABLE - 20M
A023805	SAT401 EXTENSION CABLE - 25M
A023806	SAT401 EXTENSION CABLE - 30M
A023807	SAT401 EXTENSION CABLE - 0.3M
A06802	SAT401 EXTENSION CABLE - 5M (25way)

DECLARATION OF CONFORMITY

A062801	SAT401 POWER CABLE (Cigar to DC) -2M
A058801	SAT401 PA Button (Hand Held)
CBL-000-200-S00-01	CBL, VMS BDG RDR, Weigand, 2M
CBL-000-200-S00-03	CBL, VSU Canbus, 2M
CBL-000-200-S00-05	CBL, VSU Canbus with resistor, 2M, VSU
CBL-000-240-C00	CBL,RS232,TTL OUTPUT, 1400G
CBL-000-250-C00	CBL, HSM 5V 232 TTL, 2.5M
CBL-000-300-C00	Cable: RS232 TTL OUT
CBL-000-300-C00-01	RS232TTL OUT, INDUSTRIAL
CBL-000-300-S00	CBL, PS-2 KBW, HSM 5V
CBL-010-300-C00	CBL, 232 TTL, 9 PIN
CBL-020-035-S00	CBL,RS232,5V,DB9
CBL-020-150-C00	1.5m RS232 host cable
CBL-020-150-S00-01	Cable, RS232 5V, 1.5M, YJ HF500
CBL-020-270-S00	2.7m RS232 host cable
CBL-020-270-S00-01	Cable, RS232 5V, 2.7M YJ HF500
CBL-020-290-S00	Cable, RS232, Black, DB9, 5V, 2.9M
CBL-020-290-S00-01	Cable, RS232, Black, DB9, 5V, 2.9M ID
CBL-020-300-C00	Cable: RS232 (5V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9
CBL-020-300-C00-01	Cable, RS232, 5V Signal, DB9F, Coiled, 3M, IND
CBL-020-300-S00	CBL,232 TTL, 5V
CBL-020-350-S00	Cable, RS232, 5V SIGNAL
CBL-020-500-C00	CBL,RS232TTL,5V SIGNAL,DB
CBL-020-500-C00-01	CBL,RS232TTL,5V SIGNAL
CBL-020-500-C00-02	CBL,RS232TTL,5V,DB9PFEMA LE,COIL,5M,UPS
CBL-020-500-S00	Cable, RS232, 5V SIGNAL, DB9
CBL-120-300-C00	Cable: RS232C (+/-12V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9
CBL-130-300-S00	Cable, TRUE232,9 PIN D
CBL-140-370-S20-BP	RS232 DB9 Female 3.7m
CBL-150-650-S00	Drawing, CBL, RS232, 12V, 7820
CBL-200-200-S00	Cable, VSU to USB DB9, 2M, VMS
CBL-200-300-C00	Cable: HSM, 5V 232 TTL

DECLARATION OF CONFORMITY

CBL-200-300-S00	CBL, RS232,DB9 male (3m)
CBL-210-300-C00	CBL,232TTL,5V,9PIND,MALE,3M,EP,UPS
CBL-210-300-C00-01	CBL,RS232,5V,DB9MALE,3M,EP,UPS
CBL-220-300-C00	Cable: RS232 (+5V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle
CBL-220-500-S00	CBL, RS232, 5V SIGNAL, DB9
CBL-320-300-C00	Cable: RS232 (+/-12V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9
CBL-400-061-S00	CABLE RS232, 10P10C PLUG
CBL-400-150-S00	Cable is E157914 PRIMAX RU AWM 20099 60C 150V VW-1 CSA LL110529 AWM I/II A/B 60C 150V FT1
CBL-400-190-S00	HDB 15P FM to 10P10C Cable
CBL-400-250-C00	CBL, KEYBOARD EMULATION,1400G
CBL-400-250-S00-00	CBL,AUX 5V, 3310G to DATALOGIC, 2.5M
CBL-400-250-S00-02	CBL,AUX 5V, 3310G to NCR, 2.5M
CBL-400-300-C00	CBL, HSM 5V 232 TTL, AUX, 3M
CBL-400-300-S00	cable aux, 5V3310G to statos
CBL-420-300-C00	Cable: RS232 (5V signals), Honeywell Bioptic Stratos Aux, black, 10 pin modular, 3m (9.8'), coiled, host power possible (dependent upon scanner and Stratos models)
CBL-420-300-C00-01	E,RS232,5V BIOPTIC AUX,3M,INDUSTRIAL
CBL-422-300-C00	CBL,RS232 TTL 5V
CBL-431-300-S00	Cable: RS232 (+/-12V signals), Verifone Ruby, Sapphire and Topaz Terminals, black, 8 pin modular; straight, host power on pin 8
CBL-431-300-S00-01	USB TYPE A to Mini 10PIN PLUG, 2A
CBL-500-050-S00	CABLE, USB 5V, 0.5M, 3310G
CBL-500-070-S00	CABLE, USB 5V
CBL-500-100-S00-00	CABLE, MINI USB, ISLED V2
CBL-500-120-S00-00	CABLE, STANDARD MINI USB, ISLED V2
CBL-500-120-S00-01	USB Type A to Mini 10pin
CBL-500-120-S00-03	Cable, Micro USB, IA8, EDA50
CBL-500-120-S00-04	CBL, USB, Micro B to Type A
CBL-500-150-S00	USB Type A HSM 5V 1480mm straight
CBL-500-150-S00-03	CBL USB 1.5M Type A HSM 5V
CBL-500-200-C00	USB Type A HSM 5V
CBL-500-200-S00	USB Type A HSM
CBL-500-200-S00-01	Cable: CBL USB 2M, Type A, HSM

DECLARATION OF CONFORMITY

CBL-500-200-S00-02	USB A type to Micro B, 2M
CBL-500-200-S00-04	Cable, VSU to USB Type A, 2M, VMS
CBL-500-270-S00-01	CBL,USB 5V, 2.7M YJ HF500
CBL-500-290-S00	Cable, USB, Black, Type A, 5V, 2.9M
CBL-500-300-C00	Cable: USB, black, Type A, 3m (9.8'), coiled, 5V host power
CBL-500-300-C00-01	Cable, USB Type A
CBL-500-300-C00-03	Cable: USB Type A, Coiled, 3M
CBL-500-300-C00-04	Xenon RS232 cable
CBL-500-300-S00	Cable: USB, black, Type A, 3m (9.8'), straight, 5V host power
CBL-500-300-S00-02	CBL,USB W/Ferrite, Type A, HSM 5V
CBL-500-300-S00-03	CBL,USB W/Ferrite, Type A,5V Industrial
CBL-500-300-S00-04	CBL, USB Type A, HSM 5V
CBL-500-300-S00-06	CBL, USB Type A, 5V
CBL-500-300-S00-06	CBL, USB Type A, 5V, W/Ferrite
CBL-500-400-C00	Cable, USB, BLK, Type A
CBL-500-500-C00	Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power
CBL-500-500-S00	Cable, USB Type
CBL-500-700-C00	CBL, USB Type A, Coiled, 7m
CBL-501-300-S00	CBL, USB, 9PIN D Male 5V, Industrial
CBL-503-150-S00	CBL,USB RETAIL,12V KEY
CBL-503-300-C00	Cable: USB, black, 12V locking, 3m (9.8'), coiled, 5V host power
CBL-503-300-S00	Cable: USB, black, 12V locking, 3m (9.8'), straight, 5V host power
CBL-503-300-S00-01	CBL, USB, 12V KEY, 5V POWER, STRAIGHT
CBL-503-300-S00-02	CBL,USB FS Speed Cable, 3M
CBL-503-500-C00	Cable: USB, black, 12V locking, 5m (16.4'), coiled, 5V host power
CBL-510-300-S00	CBL, USB Type A, 5V, W/PWRLINK
CBL-520-290-S00	Cable, USB, Black, Type A, 5V, 2.9M ID
CBL-530-370-S20-BP	USB, Powered, 12V Locking, 3.7m
CBL-532-300-S00	Cable, USBRETAIL,12VKEY
CBL-540-370-S20-BP	USB, Non-powered, 12V
CBL-541-370-S20-BP	USB, Non-powered, Type A
CBL-600-300-S00	Cable, IBM 4683, Port 9B
CBL-600-300-S00-01	CBL, IBM 4683 Port 9D, HSM 5V
CBL-600-400-C00	Cable: IBM 46xx Port 9b, 12V Power, coiled, 4m (13.1')
CBL-601-300-S00	CBL,IBM 46893, Port 9B
CBL-640-370-S20-BP	46xx, IBM-RS485, 3.7m
CBL-700-300-S00	CBL, 232 TTL,HSM 5V
CBL-720-290-S00	Cable, KBW, Black, PS2, 5V, 2.9M
CBL-720-300-C00	Cable: KBW, black, PS2, 3m (9.8'), coiled, 5 V external power with option for host power

DECLARATION OF CONFORMITY

CBL-720-300-S00	CBL, PS-2 KBW, 5V
CBL-820-300-C00	WAND EMULATION9 Pin SQZ
CBL-821-300-C00	WAND EMULATION4 Pin SQZ
CBL-860-100-S02	CBL, EAS, Checkpoint, 7980G
CBL-860-200-S04	CBL, EAS, Sensormatic, 7980G
CBL-99X-183-SC0	CABLE,99X TO ZEBRA PRINTER
CBL-GIL-300-S00-01	CBL,RS232,TTL,HSM 5V
CBL-GIL-300-S00-02	Cable: RS232 (5V signals), Gilbarco terminal, black, DB9 Female, 3m (9.8'), straight
CBL-MAG-300-C00	CBL,232 TTL,MAGELLAN
CBL-MAG-300-S00	CBL, 232 TTL, MAGELLAN
CBL-MAG-400-C00	CBL, 232 TTL, MAGELLAN, AUX 5V Coiled
CBL-MAG-400-S00	Cable,RS232,5V SIGNAL
CBL-NCR-300-S00	Cable: RS232 (5V signals), NCR 787x, black, 8 pin modular, 3m (9.8'), straight, external power with option for 5V host power on pin 1
CBL-WNC-500-S20-BP	RS232 DB9 MALE 5M
HR-IC3RB	Cable, RS232, FOR KEYENCE
HR-IC3RC	Cable, TRUE232, 9PIN D
HR-IC3VC	Cable, KBW, COILED, 3M
HR-IC3UC	Cable, USB TYPE
HR-IC3UN	Cable, USB Type
HR-IC5UC	Cable, USB TYPE
MVC-2MPC-1B9	CABLE,IBM PORT 9,10 PINRJ45 MALE,COILE
MVC-3FPS-VR	Cable: Verifone-Ruby, black, 8-pin Mod, 0.6m (2.1'), straight, host power
MVC-3MPC-1B9	Cable: IBM 46xx, black, Port 9 4-pin SDL, 3.1m (10.2'), coiled, 9V host power
MVC-3MPC-VR	Cable: Verifone-Ruby, black, 8-pin Mod, 3.3m (10.7'), coiled, host power
MVC-3MPC-VR3750	Cable: Verifone-Ruby 3750 Terminal, black, 8-pin Mod, 3.5m (11.5'), coiled, host power
MVC-3MPS-VR	Cable: Verifone-Ruby, black, 8-pin Mod, 2.3m (7.4'), straight, host power
MVC-3MPS-VR3750	Cable: Verifone-Ruby 3750 Terminal, black, 8-pin Mod, 2.3m (7.4'), straight, host power
MX-232C-153-3	Cable: RS232, black, DB9 male, 2.9m (9.5'), straight, host power with TTL to 12V converter
VPS052CABLE	Cable, VPS VSU to USB Type A, 2M
VPS053CABLE	Cable, VPS VSU to VMC D9 (Spare) /EXTN Cable
VPS054CABLE	Cable, VPS Badge Reader (Spare), 2M
VPS054CABLE	Cable, VSU I/O Connector, 2M

DECLARATION OF CONFORMITY

Signed for and on behalf of	
Place and Date of Issue	9680 Old Bailes Road Fort Mill, SC 29707 USA 22-Aug-17
Name and Title	Don Douthit, Global Manager, Regulatory Compliance Honeywell Scanning & Mobility
Signature	