

# Printer Media Specifications



PRINTERS	LABELS & TAGS												RIBBONS				
	Core ID		Max Roll OD		Min Width		Max Width		Min Caliper		Max Caliper		Core ID		Wind	Optimal Length	
Desktop	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm		inches	m
742x	1 / 1.5	25 / 38	4.9	124	1.12	28	4.65	118	0.003	0.0762	0.0075	0.1905	0.5	13	CSO	3,588	91
PC4	1 / 1.5	25 / 38	5	127	1	25	4.65	118	0.003	0.0762	0.0075	0.1905	0.5	13	CSO	3,588	91
PC41	1 / 1.5	25 / 38	5	127	1	25	4.65	118	0.003	0.0762	0.0075	0.1905	0.5	13	CSO	3,588	91
PF8t – 0.5"	1 / 1.5	25 / 38	5	127	1	25	4.65	118	0.0024	0.0610	0.0070	0.1778	0.5	13	CSO	3,588	91
PF8t – 1"	1 / 1.5	25 / 38	5	127	1	25	4.65	118	0.0024	0.0610	0.0070	0.1778	1	25	CSO	10,800	274
PF8d	1 / 1.5	25 / 38	5	127	1	25	4.65	118	0.0024	0.0610	0.0070	0.1778	DIRECT THERMAL ONLY				
PC23d	1 / 1.5	25 / 38	5	127	0.47	12	2.36	60	0.003	0.0762	0.008	0.203	DIRECT THERMAL ONLY				
PC43d	1 / 1.5	25 / 38	5	127	0.75	19	4.65	118	0.003	0.0762	0.008	0.203	DIRECT THERMAL ONLY				
PC43t	1 / 1.5	25 / 38	5	127	0.75	19	4.65	118	0.003	0.0762	0.008	0.203	0.5 / 1	13 / 25	CSO	10,800	274
<b>Commercial</b>																	
PD4	1.5 / 3.0	38 / 76	8.38	213	1	25	4.65 <sup>2</sup>	118 <sup>2</sup>	0.0023	0.0584	0.0098	0.2489	1	25	CSI	18,000	457
PD41	1.5 / 3.0	38 / 76	7.5 <sup>1</sup> / 8.38	191 <sup>1</sup> / 213	1	25	4.65 <sup>2</sup>	118 <sup>2</sup>	0.0023	0.0584	0.0098	0.2489	1	25	CSI	18,000	457
PD42	1.5 / 3.0	38 / 76	7.5 <sup>1</sup> / 8.38	191 <sup>1</sup> / 213	1	25	4.65 <sup>2</sup>	118 <sup>2</sup>	0.0023	0.0584	0.0098	0.2489	1	25	CSI	18,000	457
<b>Mid-Range</b>																	
F2	1.5 / 3.0	38 / 76	6 <sup>3</sup> / 8.38	152 / 213 <sup>3</sup>	1	25	2.36	60	0.0025	0.0635	0.0075	0.1905	1	25	CSI	6,000 / 9,000	152 / 228
PF2i	1.5 / 3.0	38 / 76	6 <sup>3</sup> / 8.38	152 / 213 <sup>3</sup>	1	25	2.36	60	0.0025	0.0635	0.0075	0.1905	1	25	CSI	6,000 / 9,000	152 / 228
F4	1.5 / 3.0	38 / 76	6 <sup>3</sup> / 8.38	152 / 213 <sup>3</sup>	1	25	4.5	114	0.0025	0.0635	0.0075	0.1905	1	25	CSI	6,000 / 9,000	152 / 228
PF4i	1.5 / 3.0	38 / 76	6 <sup>3</sup> / 8.38	152 / 213 <sup>3</sup>	1	25	4.5	114	0.0025	0.0635	0.0075	0.1905	1	25	CSI	6,000 / 9,000	152 / 228
PF4ci	1.5 / 3.0	38 / 76	6 <sup>3</sup> / 8.38	152 / 213 <sup>3</sup>	1	25	4.5	114	0.0025	0.0635	0.0075	0.1905	1	25	CSI	6,000 / 9,000	152 / 228
PM4i	1.5 / 3.0	38 / 76	8.38	213	1	25	4.5	114	0.0025	0.0635	0.0070	0.1778	1	25	CSI	18,000	457
3400	3	76	8.38	213	0.75	19	4.5	114	0.003	0.0762	0.0100	0.2540	1	25	CSO	6,000	152
3600	3	76	8.38	213	3	76	6.7	170	0.003	0.0762	0.0100	0.2540	1	25	CSO	6,000	152
4420	3	76	8.38	213	0.75	19	4.5	114	0.003	0.0762	0.0120	0.3048	1	25	CSO	18,000	457
4440	3	76	8.38	213	0.75	19	4.5	114	0.003	0.0762	0.0120	0.3048	1	25	CSO	18,000	457

<sup>1</sup>When using internal liner take-up.

<sup>2</sup>Maximum print width is 4.09" (203dpi) and 4.17" (300dpi)

<sup>3</sup>6" Roll OD applies to long-door configuration, 8.38" Roll OD applies to all other configurations.

<sup>4</sup>Minimum width is 0.5" for the 4400C model when using the required adapter.

# Printer Media Specifications



PRINTERS	LABELS & TAGS												RIBBONS				
	Core ID		Max Roll OD		Min Width		Max Width		Min Caliper		Max Caliper		Core ID		Wind	Optimal Length	
High Performance	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm			inches
PX4i	1.5 / 3.0	38 / 76	8.38	213	1	25	4.72	120	0.0024	0.0610	0.0100	0.2540	1	25	CSI	18,000	457
PX6i	1.5 / 3.0	38 / 76	8.38	213	3	76	6.7	170	0.0024	0.0610	0.0100	0.2540	1	25	CSI	18,000	457
<b>Specialty</b>																	
PA30	n/a <sup>5</sup>	n/a <sup>5</sup>	n/a <sup>5</sup>	n/a <sup>5</sup>	2	51	4.72	120	0.0024	0.0610	0.0100	0.2540	1	25	CSI	24,000	610
3240	3	76	8.38	213	0.5	13	2.8	71	0.003	0.0762	0.0120	0.3048	1	25	CSO	6,000	152
<b>Mobile</b>																	
PB2	0.4	10	1.5	38	2.25	57	2.25	57	0.002	0.0508	0.0040	0.1016	DIRECT THERMAL ONLY				
PB3	0.4	10	1.375	35	3.125	79	3.125	79	0.002	0.0508	0.0040	0.1016					
PB42	0.75	19	2.65	67	4.375	111	4.375	111	0.002	0.0508	0.0044	0.1118					
PB50	0.75	19	2.65	67	2	51	4.375	111	0.002	0.0508	0.0065	0.1651					
PW50 <sup>6</sup>	0.75	19	2.65	67	4.375	111	4.375	111	0.002	0.0508	0.0044	0.1118					
PB21	0.75	19	2.25	57	2.25	57	2.25	57	0.002	0.0508	0.0044	0.1118					
PB22	0.75	19	2.25	57	1	25	2.25	56	0.002	0.0508	0.0065	0.1651					
PB31	0.75	19	2.65	57	3.3	84	3.25	84	0.002	0.0508	0.0044	0.1118					
PB32	0.75	19	2.65	67	1.2	30	3.25	84	0.002	0.0508	0.0065	0.1651					

<sup>5</sup> Roll OD, Core ID, and Roll length are dependent upon the applicator system being used

<sup>6</sup> 0.4" with optional adapter