



## Material Product Datasheet

L6473028

Duratran II Piggyback Label

### FACE STOCK

Description	Thermal Transfer Paper
Caliper Target (mils)	3
MD Tensile Target (lb/in)	28
CD Tensile Target (lb/in)	17

### ADHESIVE

Description	Acrylic Permanent
Caliper Target (mils)	0.8 (x2)
Peel adhesive Target on Stainless Steel (lb/in)	

### LINER

Description	40# SCK (x2)
Caliper Target (mils)	2.4 (x2)

**TOTAL CALIPER TARGET (mils)** 9.4

### ENVIRONMENT

Storage Temperature (°F)	40	to	80
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	38		
Service Temperature (°F)	-65	to	200

**Sample Part #** E27210\_S

### RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
- TMX3000 Series Resin

### COMPLIANCE

- UL
- ✓ FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

### RECOMMENDED FOR SELF-STRIP

### MAXIMUM OUTDOOR LIFE

- < 6 months
- < 12 months
- < 18 months
- 5+ Years

### TYPICAL APPLICATIONS

- ✓ Shipping / Receiving
- ✓ Work in Process (WIP)
- ✓ Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- Asset / Tool Marking

### Special Notes

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.