



Material Product Datasheet

L6101099

Duratron II Semi-gloss Paper Label

FACE STOCK

Description	54# Semi-gloss Paper
Caliper Target (mils)	2.6
MD Tensile Target (lb/in)	30
CD Tensile Target (lb/in)	15

ADHESIVE

Description	Acrylic Cold Temp
Caliper Target (mils)	0.8
Peel adhesive Target on Stainless Steel (lb/in)	

LINER

Description	40# CK
Caliper Target (mils)	2.4

TOTAL CALIPER TARGET (mils) 5.8

ENVIRONMENT

Storage Temperature (°F)	40	to	80
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	-20		
Service Temperature (°F)	-65	to	200

Sample Part

Special Notes

Labels for applications requiring a semi-gloss finish

RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
- TMX3000 Series Resin

COMPLIANCE

- UL
- ✓ FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

RECOMMENDED FOR SELF-STRIP



MAXIMUM OUTDOOR LIFE

- < 6 months
- < 12 months
- < 18 months
- 5+ Years

TYPICAL APPLICATIONS

- ✓ Shipping / Receiving
- ✓ Work in Process (WIP)
- ✓ Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- Asset / Tool Marking

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.