



Material Product Datasheet

L1060010

Duratran II Synthetic Value Tag

FACE STOCK

Description Thermal Transfer Film

Caliper Target (mils) 7.5

MD Tensile Target (lb/in) 30

CD Tensile Target (lb/in) 33

ADHESIVE

Description N/A

Caliper Target (mils) 0

Peel adhesive Target on
Stainless Steel (lb/in)

LINER

Description N/A

Caliper Target (mils)

TOTAL CALIPER TARGET (mils) 7.5

ENVIRONMENT

Storage Temperature (°F) 40 to 72

Storage Humidity (%) 35 to 75

Shelf Life (months) 12

Minimum Application Temp (°F) N/A

Service Temperature (°F) -70 to 200

Sample Part #

E27222_S

RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
- TMX3000 Series Resin

COMPLIANCE

- UL
- ✓ FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

RECOMMENDED FOR SELF-STRIP

NO

MAXIMUM OUTDOOR LIFE

- < 6 months
- ✓ < 12 months
- < 18 months
- 5+ Years

TYPICAL APPLICATIONS

- Shipping / Receiving
- ✓ Work in Process (WIP)
- Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- ✓ Asset / Tool Marking

Special Notes

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Honeywell Productivity Products - Printer Supplies

Printed on:
8/7/2019

9290 LeSaint Drive
Fairfield, Ohio 45014
800-755-5505 opt 2