



## Material Product Datasheet

L3501020

### Duratran KS Synthetic Paper Label

#### FACE STOCK

Description	Polypropylene
Caliper Target (mils)	3
MD Tensile Target (lb/in)	34
CD Tensile Target (lb/in)	72

#### ADHESIVE

Description	Acrylic Permanent
Caliper Target (mils)	0.7
Peel adhesive Target on Stainless Steel (lb/in)	

#### LINER

Description	40# SCK
Caliper Target (mils)	2.4

**TOTAL CALIPER TARGET (mils)** 6.1

#### ENVIRONMENT

Storage Temperature (°F)	35	to	75
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	25		
Service Temperature (°F)	-75	to	200

**Sample Part #**

E25742\_S

#### RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
- TMX3000 Series Resin

#### COMPLIANCE

- UL
- ✓ FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

#### RECOMMENDED FOR SELF-STRIP

#### MAXIMUM OUTDOOR LIFE

- ✓ < 6 months
- < 12 months
- < 18 months
- 5+ Years

#### TYPICAL APPLICATIONS

- Shipping / Receiving
- Work in Process (WIP)
- ✓ Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- ✓ Asset / Tool Marking

#### Special Notes

Durable label at an economical price point. Common applications include: Horticultural labeling, Chemical drum labels, Medical device and specimen labeling, Industrial bin labels, Automotive component labeling

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Honeywell Productivity Products - Printer Supplies

Printed on:  
3/14/2019

9290 LeSaint Drive  
Fairfield, Ohio 45014  
800-755-5505 opt 2