



Material Product Datasheet

L8000071

Duratran DuraTuff Film Tag

FACE STOCK

Description	Polyolefin Film Tag
Caliper Target (mils)	8
MD Tensile Target (lb/in)	
CD Tensile Target (lb/in)	

ADHESIVE

Description	N/A
Caliper Target (mils)	0
Peel adhesive Target on Stainless Steel (lb/in)	

LINER

Description	N/A
Caliper Target (mils)	0

TOTAL CALIPER TARGET (mils) 0

ENVIRONMENT

Storage Temperature (°F)	40	to	80
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	n/a		
Service Temperature (°F)	-60	to	200

Sample Part # E23683_S

RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
TMX3000 Series Resin

COMPLIANCE

- UL
- ✓ FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

RECOMMENDED FOR SELF-STRIP

MAXIMUM OUTDOOR LIFE

- < 6 months
- ✓ < 12 months
- < 18 months
- 5+ Years

TYPICAL APPLICATIONS

- Shipping / Receiving
- ✓ Work in Process (WIP)
- Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- Asset / Tool Marking

Special Notes

Durable moisture resistant tagging. Examples: Nursery & horticulture tags, lumber tags, furniture/bedding law tags, steel tags, brick tags.

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Honeywell Productivity Products - Printer Supplies