



Material Product Datasheet

L6003020

Duratran II Cold Temp Label

FACE STOCK

Description	Thermal Transfer Paper
Caliper Target (mils)	2.9
MD Tensile Target (lb/in)	26
CD Tensile Target (lb/in)	17

ADHESIVE

Description	Acrylic Cold Temp
Caliper Target (mils)	0.8
Peel adhesive Target on Stainless Steel (lb/in)	

LINER

Description	40# CK
Caliper Target (mils)	2.4

TOTAL CALIPER TARGET (mils) 6.1

ENVIRONMENT

Storage Temperature (°F)	40	to	80
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	-20		
Service Temperature (°F)	-65	to	200

Sample Part # E27439_S
E19420_S

Special Notes

Cold Storage Labeling
Frozen Food Labeling and Shipment

RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
TMX3000 Series Resin

COMPLIANCE

UL
FDA.21 CFR 175.105
CSA
cUL
BPA-Free
FSC-Certified

RECOMMENDED FOR SELF-STRIP ✓

MAXIMUM OUTDOOR LIFE

< 6 months
< 12 months
< 18 months
5+ Years

TYPICAL APPLICATIONS

- ✓ Shipping / Receiving
- ✓ Work in Process (WIP)
- ✓ Rack / Shelf / Bin
Durable Goods
Lock out / Tag out (LOTO)
Asset / Tool Marking

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.