



Material Product Datasheet

L3313000

Duratran II Thermal Transfer Gloss Label

FACE STOCK

Description	Gloss Polypropylene
Caliper Target (mils)	2.6
MD Tensile Target (lb/in)	14
CD Tensile Target (lb/in)	80

ADHESIVE

Description	Acrylic Permanent
Caliper Target (mils)	0.7
Peel adhesive Target on Stainless Steel (lb/in)	

LINER

Description	40# SCK
Caliper Target (mils)	2.4

TOTAL CALIPER TARGET (mils) 5.7

ENVIRONMENT

Storage Temperature (°F)	35	to	75
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	25		
Service Temperature (°F)	-112	to	200

Sample Part #

E27212_S

RIBBON COMPATIBILITY

- TMX1000 Series Wax
- TMX2000 Series Mid-Range
- ✓ TMX3000 Series Resin

COMPLIANCE

- UL
- ✓ FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

RECOMMENDED FOR SELF-STRIP

MAXIMUM OUTDOOR LIFE

- ✓ < 6 months
- < 12 months
- < 18 months
- 5+ Years

TYPICAL APPLICATIONS

- Shipping / Receiving
- Work in Process (WIP)
- Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- Asset / Tool Marking

Special Notes

Durable labeling, Moderate duration outdoor labeling, Medical labeling, Labels for cryogenic exposure or storage, Horticultural labels

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Honeywell Productivity Products - Printer Supplies

Printed on:
3/14/2019

9290 LeSaint Drive
Fairfield, Ohio 45014
800-755-5505 opt 2