



## Material Product Datasheet

L6003038  
Duratran II Label

### FACE STOCK

Description	Thermal Transfer Paper
Caliper Target (mils)	2.8
MD Tensile Target (lb/in)	26
CD Tensile Target (lb/in)	17

### ADHESIVE

Description	Acrylic Permanent
Caliper Target (mils)	0.9
Peel adhesive Target on Stainless Steel (lb/in)	

### LINER

Description	40# CK
Caliper Target (mils)	2.4

**TOTAL CALIPER TARGET (mils)** 6.1

### ENVIRONMENT

Storage Temperature (°F)	40	to	80
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	30		
Service Temperature (°F)	-65	to	200

### Sample Part #

E06175\_S  
E07516\_S  
E15527\_S

### RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
- TMX3000 Series Resin

### COMPLIANCE

- UL
- FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- ✓ FSC-Certified

### RECOMMENDED FOR SELF-STRIP



### MAXIMUM OUTDOOR LIFE

- < 6 months
- < 12 months
- < 18 months
- 5+ Years

### TYPICAL APPLICATIONS

- ✓ Shipping / Receiving
- ✓ Work in Process (WIP)
- ✓ Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- ✓ Asset / Tool Marking

### Special Notes

General Purpose Labeling, Shipping and Logistics, Inventory Control, WIP, Asset Tracking

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Honeywell Productivity Products - Printer Supplies

Printed on:  
3/14/2019

9290 LeSaint Drive  
Fairfield, Ohio 45014  
800-755-5505 opt 2