



Material Product Datasheet

L3503062

Duratran Syntran Label

FACE STOCK

Description Matte Polyethylene

Caliper Target (mils) 3.6

MD Tensile Target (lb/in)

CD Tensile Target (lb/in)

ADHESIVE

Description Rubber Based High Tack

Caliper Target (mils) 1.7

Peel adhesive Target on
Stainless Steel (lb/in)

LINER

Description 50# N LF

Caliper Target (mils) 3.2

TOTAL CALIPER TARGET (mils) 8.5

ENVIRONMENT

Storage Temperature (°F) 40 to 80

Storage Humidity (%) 35 to 75

Shelf Life (months) 12

Minimum Application Temp (°F) 35

Service Temperature (°F) -20 to 220

Sample Part #

E13277_S

RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
- TMX3000 Series Resin

COMPLIANCE

- UL
- ✓ FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

RECOMMENDED FOR SELF-STRIP

NO

MAXIMUM OUTDOOR LIFE

- < 6 months
- ✓ < 12 months
- < 18 months
- 5+ Years

TYPICAL APPLICATIONS

- Shipping / Receiving
- Work in Process (WIP)
- ✓ Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- ✓ Asset / Tool Marking

Special Notes

Horticultural products (stake, pot, container labeling), drum labels, industrial bin labeling, oil and gas industry labeling, building products labeling, automotive components, asset tracking.

Aggressive adhesive overcomes internal bond strength on many surfaces, enabling use as tamper-evident label.

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Honeywell Productivity Products - Printer Supplies

Printed on:
8/6/2019

9290 LeSaint Drive
Fairfield, Ohio 45014
800-755-5505 opt 2