



Material Product Datasheet

L3202005

FanTastock Gloss Clear Polyester Label

FACE STOCK

Description Gloss Polyester

Caliper Target (mils) 2

MD Tensile Target (lb/in)

CD Tensile Target (lb/in)

ADHESIVE

Description Acrylic Permanent

Caliper Target (mils) 0.9

Peel adhesive Target on
Stainless Steel (lb/in)

LINER

Description 50# SCK

Caliper Target (mils) 3.1

TOTAL CALIPER TARGET (mils) 6

ENVIRONMENT

Storage Temperature (°F) 40 to 80

Storage Humidity (%) 35 to 75

Shelf Life (months) 12

Minimum Application Temp (°F) 50

Service Temperature (°F) -40 to 302

Sample Part # E27213_S

RIBBON COMPATIBILITY

TMX1000 Series Wax

TMX2000 Series Mid-Range

✓ TMX3000 Series Resin

COMPLIANCE

UL

✓ FDA.21 CFR 175.105

CSA

cUL

BPA-Free

FSC-Certified

RECOMMENDED FOR SELF-STRIP

YES

MAXIMUM OUTDOOR LIFE

< 6 months

< 12 months

< 18 months

✓ 5+ Years

TYPICAL APPLICATIONS

Shipping / Receiving

Work in Process (WIP)

✓ Rack / Shelf / Bin

✓ Durable Goods

Lock out / Tag out (LOTO)

✓ Asset / Tool Marking

Special Notes

Automotive components, Aerospace components, Electronics labeling, Protective overlaminating, Industrial bins, Medical device labeling, Suitable overlaminate for MIL-PRF-61002 labels

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Honeywell Productivity Products - Printer Supplies

9290 LeSaint Drive

Fairfield, Ohio 45014

800-755-5505 opt 2

Printed on:
8/1/2019