



Material Product Datasheet

L1060009
7.5 mil Duratran Pro Tag

FACE STOCK

Description	Thermal Transfer Film
Caliper Target (mils)	7.5
MD Tensile Target (lb/in)	42
CD Tensile Target (lb/in)	45

ADHESIVE

Description	N/A
Caliper Target (mils)	0
Peel adhesive Target on Stainless Steel (lb/in)	

LINER

Description	N/A
Caliper Target (mils)	

TOTAL CALIPER TARGET (mils) 7.5

ENVIRONMENT

Storage Temperature (°F)	40	to	72
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	N/A		
Service Temperature (°F)	-70	to	180

Sample Part #

E12982_S

RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
- TMX3000 Series Resin

COMPLIANCE

- UL
- FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

RECOMMENDED FOR SELF-STRIP

NO

MAXIMUM OUTDOOR LIFE

- < 6 months
- ✓ < 12 months
- < 18 months
- 5+ Years

TYPICAL APPLICATIONS

- Shipping / Receiving
- ✓ Work in Process (WIP)
- Rack / Shelf / Bin
- Durable Goods
- ✓ Lock out / Tag out (LOTO)
- ✓ Asset / Tool Marking

Special Notes

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.